

Compact, extremely precise and easy to clean.

Feature packed | 1000% shock overload protection
Internal rechargeable battery | 304 Stainless Steel

Doran. Powering Performance.

doran®

800.365.0084 | doranscales.com

PC-400 SERIES SS SCALE

A general purpose scale that is rugged, compact, portable, and easy-to-clean, with the case and plater constructed of food-grade stainless steel. Precision weighments with innovative design includes a Quad-Spring shockproof base and Auto Shut-Off.



PC-400 SERIES

SS Bench Scale

The PC-400 is part of a complete line of high-quality general purpose scales, designed to be durable and highly accurate, with innovative performance features that improve productivity.

Constructed entirely of 304 stainless steel and designed to be wipe down safe. Extremely precise, with weigh-in as fine as 0.1 gram. Large LCD read-out display. Recharge the battery in less than four hours with the AC adapter and the scale can also be used while recharging. The auto shut-off feature maximizes battery life.

INNOVATIVE DESIGN AND PERFORMANCE FEATURES

- Weight is quickly locked-on and displayed with Doran exclusive Weight Lock technology.
- Quad-Spring shockproof base design that virtually eliminates damage from 1000% overload shock or static.
- Lightweight and portable with exceptional build quality.
- Programmable auto shutoff feature.
- Battery or AC power for continuous operation.
- Low Battery indicator. Battery life is 15 hours of continuous use.
- Adjustable feet to maintain stability.
- Quickly switch between lb, kg, g, oz, or lb:oz.

THREE-BUTTON CONTROLS

POWER On/Off with adjustable automatic shutoff timer for battery power applications.

ZERO used to zero-out the weight of packaging or other elements not to be included in the product weight.

UNIT button to set weight by lb, kg, g, oz, or lb:oz.



SPECIFICATIONS

Warranty:	Scale: One Year Battery: 90 Days
Approvals:	NTEP
Power:	Internal rechargeable battery and wall mounted UL Approved AC transformer standard
Serial Interface:	Bi-directional RS-232
Controls:	On/Off, Zero, and Units
Units:	lb, kg, g, oz, or lb:oz
Temperature Range:	14° to 104° F (-10° to +40° C)
System Linearity:	0.01% full scale
Dimensions:	Overall: 8.75" L x 6.5" W x 2" Platter: 6.5" x 6.5"
Weight Capacity:	Model PC400-02 2 x 0.0002 lb (1000 x 0.1 g) Model PC400-02LFT 2 x 0.001 lb (2300 x 0.5 g) Model PC400-05 5 x 0.002 lb (2300 x 1 g) Model PC400-10 10 x 0.005 lb (4500 x 2 g) Model PC400-20 20 x 0.01 lb (9100 x 5 g)